










**SPECIFICATIONS**

	<b>GEOLOGY</b>	Sandstone
	<b>TYPE</b>	100% Bedface
	<b>PATTERN</b>	1:1 Coursed
	<b>HEIGHTS</b>	2-1/2"
	<b>LENGTHS</b>	3" - 20" (boxed); 3" - 26" (crated material can exceed 20")
	<b>DEPTHS</b>	3/4" to 1-1/4"
	<b>COLORS</b>	Gray-Grey
	<b>COVERAGE</b>	Available in thin veneer only.
	<b>WEIGHT</b>	12.5 lbs. per square foot
	<b>FLATS</b>	10 s/f Box, 100 s/f Crate, 180 s/f Crate
	<b>CORNERS</b>	10 In/ft Box, 100 In/ft Crate
	<b>NOTES</b>	Packaged assuming tight-fit installation.

**ASTM C-97**

Water Absorption %	.12 psi
Bulk Specific Gravity	2.78 psi

**ASTM C-170**

Parallel to Rift, Dry	14214 psi
Parallel to Rift, Wet	14213 psi
Perpendicular to Rift, Dry	21814 psi
Perpendicular to Rift, Wet	21320 psi

**ASTM C-99**

Parallel to Rift, Dry	3046 psi
Parallel to Rift, Wet	3191 psi

**ASTM C-880**

Perpendicular to Rift, Dry	4351 psi
Perpendicular to Rift, Wet	4351 psi



**GOLD QUARRIER**  
ANSI/NSC 373-2013  
C0290908-101



**GOLD FABRICATOR**  
ANSI/NSC 373-2013  
C0289215-101